

Environmental Protection Agency

§ 98.244

12 = Atomic weight of carbon (C) (kg/kg-mole).

(d) *Optional combustion methodology for ethylene production processes.* For each ethylene production process, calculate GHG emissions from combustion units that burn fuel that contains any off-gas from the ethylene process as specified in paragraphs (d)(1) through (d)(5) of this section.

(1) Except as specified in paragraphs (d)(2) and (d)(5) of this section, calculate CO₂ emissions using the Tier 3 or Tier 4 methodology in subpart C of this part.

(2) You may use either Equation C-1 or Equation C-2a in subpart C of this part to calculate CO₂ emissions from combustion of any ethylene process off-gas streams that meet either of the conditions in paragraphs (d)(2)(i) or (d)(2)(ii) of this section (for any default values in the calculation, use the defaults for fuel gas in Table C-1 of subpart C of this part). Follow the otherwise applicable procedures in subpart C to calculate emissions from combustion of all other fuels in the combustion unit.

(i) The annual average flow rate of fuel gas (that contains ethylene process off-gas) in the fuel gas line to the combustion unit, prior to any split to individual burners or ports, does not exceed 345 standard cubic feet per minute at 60 °F and 14.7 pounds per square inch absolute, and a flow meter is not installed at any point in the line supplying fuel gas or an upstream common pipe. Calculate the annual average flow rate using company records assuming total flow is evenly distributed over 525,600 minutes per year.

(ii) The combustion unit has a maximum rated heat input capacity of less than 30 mmBtu/hr, and a flow meter is not installed at any point in the line supplying fuel gas (that contains ethylene process off-gas) or an upstream common pipe.

(3) Except as specified in paragraph (d)(5) of this section, calculate CH₄ and N₂O emissions using the applicable procedures in § 98.33(c) for the same tier methodology that you used for calculating CO₂ emissions.

(i) For all gaseous fuels that contain ethylene process off-gas, use the emission factors for “Petroleum” in Table

C-2 of subpart C of this part (General Stationary Fuel Combustion Sources).

(ii) For Tier 3, use either the default high heat value for fuel gas in Table C-1 of subpart C of this part or a calculated HHV, as allowed in Equation C-8 of subpart C of this part.

(4) You are not required to use the same Tier for each stationary combustion unit that burns ethylene process off-gas.

(5) For each flare, calculate CO₂, CH₄, and N₂O emissions using the methodology specified in §§ 98.253(b)(1) through (b)(3).

[74 FR 56374, Oct. 30, 2009, as amended at 75 FR 79157, Dec. 17, 2010]

§ 98.244 Monitoring and QA/QC requirements.

(a) If you use CEMS to determine emissions from process vents, you must comply with the procedures specified in § 98.34(c).

(b) If you use the mass balance methodology in § 98.243(c), use the procedures specified in paragraphs (b)(1) through (b)(4) of this section to determine feedstock and product flows and carbon contents.

(1) Operate, maintain, and calibrate belt scales or other weighing devices as described in Specifications, Tolerances, and Other Technical Requirements for Weighing and Measuring Devices NIST Handbook 44 (2009) (incorporated by reference, see § 98.7), or follow procedures specified by the measurement device manufacturer. You must recalibrate each weighing device according to one of the following frequencies. You may recalibrate either at the minimum frequency specified by the manufacturer or biennially (*i.e.*, once every two years).

(2) Operate and maintain all flow meters used for gas and liquid feedstocks and products according to the manufacturer's recommended procedures. You must calibrate each of these flow meters as specified in paragraphs (b)(2)(i) and (b)(2)(ii) of this section:

(i) You may use either the calibration methods specified by the flow meter manufacturer or an industry consensus standard method. Each flow meter must meet the applicable accuracy specification in § 98.3(i), except as

otherwise specified in §§ 98.3(i)(4) through (i)(6).

(ii) You must recalibrate each flow meter according to one of the following frequencies. You may recalibrate at the minimum frequency specified by the manufacturer, biennially (every two years), or at the interval specified by the industry consensus standard practice used.

(3) You must perform tank level measurements (if used to determine feedstock or product flows) according to one of the following methods. You may use any standard method published by a consensus-based standards organization or you may use an industry standard practice. Consensus-based standards organizations include, but are not limited to, the following: ASTM International (100 Barr Harbor Drive, P.O. Box CB700, West Conshohocken, Pennsylvania 19428–B2959, (800) 262–1373, <http://www.astm.org>), the American National Standards Institute (ANSI, 1819 L Street, NW., 6th Floor, Washington, DC 20036, (202) 293–8020, <http://www.ansi.org>), the American Gas Association (AGA, 400 North Capitol Street, NW., 4th Floor, Washington, DC 20001, (202) 824–7000, <http://www.aga.org>), the American Society of Mechanical Engineers (ASME, Three Park Avenue, New York, NY 10016–5990, (800) 843–2763, <http://www.asme.org>), the American Petroleum Institute (API, 1220 L Street, NW., Washington, DC 20005–4070, (202) 682–8000, <http://www.api.org>), and the North American Energy Standards Board (NAESB, 801 Travis Street, Suite 1675, Houston, TX 77002, (713) 356–0060, <http://www.api.org>).

(4) Beginning January 1, 2010, use any applicable methods specified in paragraphs (b)(4)(i) through (b)(4)(xiv) of this section to determine the carbon content or composition of feedstocks and products and the average molecular weight of gaseous feedstocks and products. Calibrate instruments in accordance with paragraphs (b)(4)(i) through (b)(4)(xvi), as applicable. For coal used as a feedstock, the samples for carbon content determinations shall be taken at a location that is representative of the coal feedstock used during the corresponding monthly period. For carbon black products, sam-

ples shall be taken of each grade or type of product produced during the monthly period. Samples of coal feedstock or carbon black product for carbon content determinations may be either grab samples collected and analyzed monthly or a composite of samples collected more frequently and analyzed monthly. Analyses conducted in accordance with methods specified in paragraphs (b)(4)(i) through (b)(4)(xv) of this section may be performed by the owner or operator, by an independent laboratory, or by the supplier of a feedstock.

(i) ASTM D1945–03, Standard Test Method for Analysis of Natural Gas by Gas Chromatography (incorporated by reference, *see* § 98.7).

(ii) ASTM D6060–96 (Reapproved 2001) Standard Practice for Sampling of Process Vents With a Portable Gas Chromatograph (incorporated by reference, *see* § 98.7).

(iii) ASTM D2505–88 (Reapproved 2004) Standard Test Method for Ethylene, Other Hydrocarbons, and Carbon Dioxide in High-Purity Ethylene by Gas Chromatography (incorporated by reference, *see* § 98.7).

(iv) ASTM UOP539–97 Refinery Gas Analysis by Gas Chromatography (incorporated by reference, *see* § 98.7).

(v) ASTM D3176–89 (Reapproved 2002) Standard Practice Method for Ultimate Analysis of Coal and Coke (incorporated by reference, *see* § 98.7).

(vi) ASTM D5291–02 (Reapproved 2007) Standard Test Methods for Instrumental Determination of Carbon, Hydrogen, and Nitrogen in Petroleum Products and Lubricants (incorporated by reference, *see* § 98.7).

(vii) ASTM D5373–08 Standard Test Methods for Instrumental Determination of Carbon, Hydrogen, and Nitrogen in Laboratory Samples of Coal (incorporated by reference, *see* § 98.7).

(viii) Method 8015C, Method 8021B, Method 8031, or Method 9060A (all incorporated by reference, *see* § 98.7).

(x) Performance Specification 9 in 40 CFR part 60, appendix B for continuous online gas analyzers. The 7-day calibration error test period must be completed prior to the effective date of the rule.

(xi) ASTM D2593–93 (Reapproved 2009) Standard Test Method for Butadiene

Environmental Protection Agency

§ 98.246

Purity and Hydrocarbon Impurities by Gas Chromatography (incorporated by reference, see § 98.7).

(xii) ASTM D7633-10 Standard Test Method for Carbon Black—Carbon Content (incorporated by reference, see § 98.7).

(xiii) The results of chromatographic analysis of a feedstock or product, provided that the gas chromatograph is operated, maintained, and calibrated according to the manufacturer's instructions.

(xiv) The carbon content results of mass spectrometer analysis of a feedstock or product, provided that the mass spectrometer is operated, maintained, and calibrated according to the manufacturer's instructions.

(xv) Beginning on January 1, 2010, the methods specified in paragraphs (b)(4)(xv)(A) and (B) of this section may be used as alternatives for the methods specified in paragraphs (b)(4)(i) through (b)(4)(xiv) of this section.

(A) An industry standard practice for carbon black feedstock oils and carbon black products.

(B) Modifications of existing analytical methods or other methods that are applicable to your process provided that the methods listed in paragraphs (b)(4)(i) through (b)(4)(xiv) of this section are not appropriate because the relevant compounds cannot be detected, the quality control requirements are not technically feasible, or use of the method would be unsafe.

[74 FR 56374, Oct. 30, 2009, as amended at 75 FR 79158, Dec. 17, 2010]

§ 98.245 Procedures for estimating missing data.

For missing feedstock flow rates, product flow rates, and carbon contents, use the same procedures as for missing flow rates and carbon contents for fuels as specified in § 98.35.

§ 98.246 Data reporting requirements.

In addition to the information required by § 98.3(c), each annual report must contain the information specified in paragraphs (a), (b), or (c) of this section, as appropriate for each process unit.

(a) If you use the mass balance methodology in § 98.243(c), you must report the information specified in paragraphs

(a)(1) through (a)(11) of this section for each type of petrochemical produced, reported by process unit.

(1) The petrochemical process unit ID number or other appropriate descriptor.

(2) The type of petrochemical produced, names of other products, and names of carbon-containing feedstocks.

(3) Annual CO₂ emissions calculated using Equation X-4 of this subpart.

(4) Each of the monthly volume, mass, and carbon content values used in Equations X-1 through X-3 of this subpart (*i.e.*, the directly measured values, substitute values, or the calculated values based on other measured data such as tank levels or gas composition) and the molecular weights for gaseous feedstocks and products used in Equation X-1 of this subpart, and the temperature (in °F) at which the gaseous feedstock and product volumes used in Equation X-1 of this subpart were determined. Indicate whether you used the alternative to sampling and analysis specified in § 98.243(c)(4).

(5) Annual quantity of each type of petrochemical produced from each process unit (metric tons).

(6) Name of each method listed in § 98.244 used to determine a measured parameter (or description of manufacturer's recommended method).

(7) [Reserved]

(8) Identification of each combustion unit that burned both process off-gas and supplemental fuel.

(9) If you comply with the alternative to sampling and analysis specified in § 98.243(c)(4), the amount of time during which off-specification product was produced, the volume or mass of off-specification product produced, and if applicable, the date of any process change that reduced the composition to less than 99.5 percent.

(10) You may elect to report the flow and carbon content of wastewater, and you may elect to report the annual mass of carbon released in fugitive emissions and in process vents that are not controlled with a combustion device. These values may be estimated based on engineering analyses. These values are not to be used in the mass balance calculation.